



14" x 40", 3 HP, 230V, 3-Phase (GH-1440-3)

Product Images



Additional Information

Stock Number	JT1-2710
Bed Gap (In.)	8
Carriage Travel (In.)	35
Compound Slide Travel (In.)	6.45
Cross Slide Travel (In.)	6.7
Distance Between Centers (In.)	40
Drive	Geared Head
Length of Gap (In.)	7-2/3
Max Tool Size (In.)	5/8 x 5/8
Model Number	GH-1340
Motor Phase	3
Motor Power (HP)	3
Motor Voltage (V.)	230
Number of Inch Threads	32
Number of Longitudinal and Cross Feed Rates	40
Number of Metric Threads	32
Number of Spindle Speeds	16
Overall Dimensions (L x W x H) (In.)	76 x 30 x 48
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0005" – 0.0086"
Range of Inch Threads (TPI)	4-56
Range of Longitudinal Feeds (IPR)	0.0016" – 0.0257"
Range of Metric Threads	0.4 – 7mm
Range of Spindle Speeds (RPM)	45-1800

Size	13 x 40
Spindle Bore (In.)	1-3/8
Spindle Mount	D1-5
Spindle Taper	MT6
Spindle Taper with Sleeve	MT-4
Steady Rest Capacity (In.)	2-3/4
Style (Type)	Bench - Geared Head
Swing Over Bed (In.)	14
Swing Over Cross Slide (In.)	8.7"
Swing Through Gap (In.)	20.3"
Tailstock Spindle Travel (In.)	3-3/4
Taper in Tailstock Spindle	MT-3
Warranty	2 Year
Width of Bed (In.)	8"
Gross Weight	1236.0
Net Weight	1154.0