



J-2500, 15" Floor Model Drill Press 115V 1Ph

Product Images





Short Description

JET J-2500, 15-Inch Drill Press, 115V 1Ph (354400)

Additional Information

Stock Number	JT9-354400
Base Dimensions (In.)	11 x 19-1/2
Column Diameter (In.)	2-7/8
Distance Column to Spindle (In.)	7-1/2
Drilling Capacity Cast Iron (In.)	5/8
Drilling Capacity Mild Steel (In.)	1/2
Drills to Center of Circle (In.)	15
Model Number	J-2500
Motor (HP)	3/4 HP, 115/230V, 1Ph
Number of Spindle Speeds	16
Overall Dimensions (L x W x H) (In.)	31 x 13 x 63
Prop 65	Cancer and Reproductive Harm
Range of Spindle Speeds (RPM)	200, 290, 350, 430, 500, 580, 640, 720, 800, 870, 1,440, 1,630, 1,820, 2,380, 2,540, 3,630
Range of Spindle Speeds (RPM) Spindle Distance to Base (In.)	
	1,440, 1,630, 1,820, 2,380, 2,540, 3,630
Spindle Distance to Base (In.)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24 MT-2
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24 MT-2 3-3/8
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24 MT-2 3-3/8 Belt Drive
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type) T-Slots Number and Size (In.)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24 MT-2 3-3/8 Belt Drive 3 - 5/8
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type) T-Slots Number and Size (In.) Table Size (L x W) (In.)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24 MT-2 3-3/8 Belt Drive 3 - 5/8 11-1/2 x 11-1/2
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type) T-Slots Number and Size (In.) Table Size (L x W) (In.) Table Travel (In.)	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24 MT-2 3-3/8 Belt Drive 3 - 5/8 11-1/2 x 11-1/2
Spindle Distance to Base (In.) Spindle Distance to Table (Max.) (In.) Spindle Taper (In. x TPI) Spindle Travel (In.) Style (Type) T-Slots Number and Size (In.) Table Size (L x W) (In.) Table Travel (In.) Warranty	1,440, 1,630, 1,820, 2,380, 2,540, 3,630 48 24 MT-2 3-3/8 Belt Drive 3 - 5/8 11-1/2 x 11-1/2 24 2 Year

Gross Weight

