



EVS-1440 Electronic Variable Speed lathe with Newall DP700 DRO, Taper Attachment & Collet Closer, 3HP

Product Images



Short Description

EVS-1440 Electronic Variable Speed lathe with Newall DP700 DRO, Taper Attachment & Collet Closer, 3HP, 230, 3Ph

Additional Information

Stock Number	JT9-311451
Compound Slide Travel (In.)	3-1/2
Cross Slide Travel (In.)	7
Length of Gap (In.)	9-1/2
Max Tool Size (In.)	3/4 x 3/4
Model Number	EVS-1440B
Motor (HP)	3HP, 230V, 3Ph
Number of Inch Threads	34.0000
Number of Longitudinal and Cross Feed Rates	25
Number of Metric Threads	34.0000
Overall Dimensions (L x W x H) (In.)	68.5 x 28.3 x 50
Prop 65	None
Range of Inch Threads (TPI)	2-56
Range of Longitudinal Feeds (IPR)	0.0016-0.0460
Range of Metric Threads	0.5-12
Range of Spindle Speeds (RPM)	40-2000
Spindle Bore (In.)	1-1/2
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	0.23-0.61 Copper Shaft (Standard) 0.20-2.36 Bearing Roller(OP)
Swing Over Bed (In.)	14
Swing Over Cross Slide (In.)	9-1/16
Tailstock Spindle Travel (In.)	6-1/8
Taper in Tailstock Spindle	MT-3

Warranty	2 Year
Width of Bed (In.)	7.48
Gross Weight	1584.0
Net weight	1320.0