



# GHB-1236 Geared Head Bench Lathe with ACU\_RITE 203 DRO & Taper Attachment in Jet Metalworking, Turning, Lathes

## Product Images

---



## Short Description

---

GHB-1236 Geared Head Bench Lathe with ACU\_RITE 203 DRO & Taper Attachment in Jet Metalworking, Turning, Lathes

## Additional Information

---

Stock Number	JT9-323235
Carriage Travel (In.)	27-3/8
Compound Slide Travel (In.)	3
Length of Gap (In.)	8-3/4
Max Tool Size (In.)	3/4 x 3/4
Model Number	GHB-1236
Motor (HP)	2HP, 230V, Single Phase
Number of Inch Threads	36.0000
Number of Longitudinal and Cross Feed Rates	48/36
Number of Metric Threads	32.0000
Number of Spindle Speeds	9
Overall Dimensions (L x W x H) (In.)	66-1/64 x 29-1/2 x 59-13/16
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0014 - 0.0116
Range of Inch Threads (TPI)	4-60
Range of Longitudinal Feeds (IPR)	0.0019 - 0.0472
Range of Metric Threads	0.4-7mm
Range of Spindle Speeds (RPM)	75 - 1400
Spindle Bore (In.)	1.575
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	0.31-2.95
Swing Over Bed (In.)	12
Swing Over Cross Slide (In.)	7-1/2

Swing Through Gap (In.)	18
Tailstock Spindle Travel (In.)	3-1/2
Taper in Tailstock Spindle	MT-3
Weight (Lbs.)	1210
Width of Bed (In.)	7.12
Gross Weight	1297.0

