




## GH-1440-3 Lathe with Taper Attachment

## **Product Images**



## **Short Description**

GH-1440-3 Lathe with Taper Attachment and Collet Closer

## **Additional Information**

Stock Number	JT9-323401
Carriage Travel (In.)	37-1/2
Compound Slide Travel (In.)	3-1/2
Length of Gap (In.)	9-3/8
Max Tool Size (In.)	5/8 x 5/8
Model Number	GH-1440-3
Motor (HP)	3HP, 230/460V, 3PH
Number of Inch Threads	40.0000
Number of Longitudinal and Cross Feed Rates	40
Number of Metric Threads	23.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	74-4/5 x 28 x 46
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0004 - 0.0103
Range of Inch Threads (TPI)	4-112
Range of Longitudinal Feeds (IPR)	0.0012 - 0.0294
Range of Metric Threads	0.45-7.5
Range of Spindle Speeds (RPM)	40-1800
Spindle Bore (In.)	1-1/2
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	3-1/2
Swing Over Bed (In.)	14
Swing Over Cross Slide (In.)	8-1/5

Swing Through Gap (In.)	20
Tailstock Spindle Travel (In.)	4-3/4
Taper in Tailstock Spindle	MT-3
Warranty	2 Year
Weight (Lbs.)	2336
Width of Bed (In.)	10-1/5
Gross Weight	2336.0

