



GH-1440-3 Lathe with Newall NMS300 DRO and Collet Closer

Product Images



Short Description

GH-1440-3 Lathe with Newall DP500 DRO and Collet Closer

Additional Information

Stock Number	JT9-323416
Carriage Travel (In.)	37-1/2
Compound Slide Travel (In.)	3-1/2
Length of Gap (In.)	9-3/8
Max Tool Size (In.)	5/8 x 5/8
Model Number	GH-1440-3
Motor (HP)	3HP, 230/460V, 3PH
Number of Inch Threads	40.0000
Number of Longitudinal and Cross Feed Rates	40
Number of Metric Threads	23.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	74-4/5 x 28 x 46
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	0.0004 - 0.0103
Range of Inch Threads (TPI)	4-112
Range of Longitudinal Feeds (IPR)	0.0012 - 0.0294
Range of Metric Threads	0.45-7.5
Range of Spindle Speeds (RPM)	40-1800
Shipping Dimensions (L x W x H) (In.)	78-2/5 x 30 x 55
Spindle Bore (In.)	1-1/2
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	3-1/2
Swing Over Bed (In.)	14

Swing Over Cross Slide (In.)	8-1/5
Swing Through Gap (In.)	20
Tailstock Spindle Travel (In.)	4-3/4
Taper in Tailstock Spindle	MT-3
Warranty	2 Year
Width of Bed (In.)	10-1/5
Gross Weight	2336.0
Net weight	2116.0