



# GHB-1340A With CBS-1340A Stand

## Product Images

---



## Short Description

---

GHB-1340A With CBS-1340A Stand

## Additional Information

---

Stock Number	JT9-321101AK
Carriage Travel (In.)	35
Compound Slide Travel (In.)	2-11/16
Drive	Geared Head
Length of Gap (In.)	8
Max Tool Size (In.)	5/8 x 5/8
Model Number	GHB-1340A
Motor (HP)	2 HP, 230V, 1Ph
Number of Inch Threads	38.0000
Number of Longitudinal and Cross Feed Rates	40
Number of Metric Threads	23.0000
Number of Spindle Speeds	8
Overall Dimensions (L x W x H) (In.)	79 x 28-1/2 x 30
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	.0006 - .0130
Range of Inch Threads (TPI)	3-1/2 - 80
Range of Longitudinal Feeds (IPR)	.0018 - .0374
Range of Metric Threads	.45 - 10
Range of Spindle Speeds (RPM)	70 - 2,000
Size	13 x 40
Spindle Bore (In.)	1-3/8
Spindle Mount	D1-4
Spindle Taper with Sleeve	MT-5 (MT-3)
Steady Rest Capacity (In.)	2-3/4

Style (Type)	Bench - Geared Head
Swing Over Bed (In.)	13
Swing Over Cross Slide (In.)	7-25/32
Swing Through Gap (In.)	18-3/4
Tailstock Spindle Travel (In.)	3-3/4
Taper in Tailstock Spindle	MT-3
Warranty	2 Year
Weight (Lbs.)	1154
Width of Bed (In.)	7-3/8
Gross Weight	1215.0
SAP Net weight	1215.0

