



## GH-1440ZX With ACU-RITE 303 DRO With Taper Attachment

## **Product Images**



## **Short Description**

GH-1440ZX With ACU-RITE 303 DRO With Taper Attachment

## **Additional Information**

Stock Number	JT9-321303
Carriage Travel (In.)	36-9/16
Compound Slide Travel (In.)	5-1/8
Cross Slide Travel (In.)	9
Drive	Geared Head
Length of Gap (In.)	12
Max Tool Size (In.)	1 x 1
Model Number	GH-1440ZX
Motor (HP)	7-1/2 HP, 230/460, 3 Ph
Number of Inch Threads	61.0000
Number of Longitudinal and Cross Feed Rates	46/31
Number of Metric Threads	24.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (ln.)	96 x 44 x 66
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	.00060360
Range of Inch Threads (TPI)	1-5/8 - 72
Range of Longitudinal Feeds (IPR)	.00150900
Range of Metric Threads	.05 - 20
Range of Spindle Speeds (RPM)	42 - 1,800
Size	14 x 40
Spindle Bore (In.)	3-1/8
Spindle Mount	D1-8
Spindle Taper with Sleeve	MT-7 (MT-5)
Spindle Bore (In.) Spindle Mount	3-1/8 D1-8

Steady Rest Capacity (In.)	3/8 - 7
Style (Type)	Engine - Large Spindle Bore
Swing Over Bed (In.)	14
Swing Over Cross Slide (In.)	7-5/8
Swing Through Gap (In.)	23-5/8
Tailstock Spindle Travel (In.)	6
Warranty	2 Year
Weight (Lbs.)	5187
Width of Bed (In.)	13-3/8
Gross Weight	5350.0

