



GH-1660ZX With Taper Attachment

Product Images



Short Description

GH-1660ZX With Taper Attachment

Additional Information

Stock Number	JT9-321477
Carriage Travel (In.)	55-9/16
Compound Slide Travel (In.)	5-1/8
Cross Slide Travel (In.)	9
Drive	Geared Head
Length of Gap (In.)	12
Max Tool Size (In.)	1 x 1
Model Number	GH-1660ZX
Motor (HP)	7-1/2 HP, 230/460, 3 Ph
Number of Inch Threads	61.0000
Number of Longitudinal and Cross Feed Rates	46/31
Number of Metric Threads	24.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	115 x 44 x 66
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	.0006 - .0360
Range of Inch Threads (TPI)	1-5/8 - 72
Range of Longitudinal Feeds (IPR)	.0015 - .0900
Range of Metric Threads	.05 - 20
Range of Spindle Speeds (RPM)	25 - 1,800
Size	16 x 60
Spindle Bore (In.)	3-1/8
Spindle Mount	D1-8
Spindle Taper with Sleeve	MT-7 (MT-5)

Steady Rest Capacity (In.)	3/8 - 7
Style (Type)	Engine - Large Spindle Bore
Swing Over Bed (In.)	16
Swing Over Cross Slide (In.)	10
Swing Through Gap (In.)	25-1/2
Tailstock Spindle Travel (In.)	5
Warranty	2 Year
Weight (Lbs.)	5795
Width of Bed (In.)	13-3/8
Gross Weight	6200.0

