



GH-1860ZX With ACU-RITE 203 DRO

Product Images



Short Description

GH-1860ZX With ACU-RITE 203 DRO

Additional Information

| | |
|---|------------------------------|
| Stock Number | JT9-321484 |
| Carriage Travel (In.) | 55-9/16 |
| Compound Slide Travel (In.) | 5-1/8 |
| Cross Slide Travel (In.) | 9 |
| Drive | Geared Head |
| Length of Gap (In.) | 12 |
| Max Tool Size (In.) | 1 x 1 |
| Model Number | GH-1860ZX |
| Motor (HP) | 7-1/2 HP, 230/460, 3 Ph |
| Number of Inch Threads | 61.0000 |
| Number of Longitudinal and Cross Feed Rates | 46/31 |
| Number of Metric Threads | 24.0000 |
| Number of Spindle Speeds | 12 |
| Overall Dimensions (L x W x H) (In.) | 115 x 44 x 66 |
| Prop 65 | Cancer and Reproductive Harm |
| Range of Cross Feeds (IPR) | .0006 - .0360 |
| Range of Inch Threads (TPI) | 1-5/8 - 72 |
| Range of Longitudinal Feeds (IPR) | .0015 - .0900 |
| Range of Metric Threads | .05 - 20 |
| Range of Spindle Speeds (RPM) | 25 - 1,800 |
| Size | 18 x 60 |
| Spindle Bore (In.) | 3-1/8 |
| Spindle Mount | D1-8 |
| Spindle Taper with Sleeve | MT-7 (MT-5) |

| | |
|--------------------------------|-----------------------------|
| Steady Rest Capacity (In.) | 3/8 - 7-3/4 |
| Style (Type) | Engine - Large Spindle Bore |
| Swing Over Bed (In.) | 18 |
| Swing Over Cross Slide (In.) | 11 |
| Swing Through Gap (In.) | 27-1/2 |
| Tailstock Spindle Travel (In.) | 5 |
| Taper in Tailstock Spindle | MT-5 |
| Warranty | 2 Year |
| Weight (Lbs.) | 6245 |
| Width of Bed (In.) | 13-1/8 |
| Gross Weight | 6700.0 |
| Net weight | 6700.0 |

