



GH-2680ZH With ACU-RITE 203 DRO

Product Images



Short Description

GH-2680ZH With ACU-RITE 203 DRO

Additional Information

Stock Number	JT9-321863
Carriage Travel (In.)	72-1/2
Compound Slide Travel (In.)	5-1/2
Drive	Geared Head
Length of Gap (In.)	8
Max Tool Size (In.)	1-1/4 x 1-1/4
Model Number	GH-2680ZH
Motor (HP)	10 HP, 230/460, 3 Ph
Number of Inch Threads	48.0000
Number of Longitudinal and Cross Feed Rates	65
Number of Metric Threads	22.0000
Number of Spindle Speeds	12
Overall Dimensions (L x W x H) (In.)	138 x 43 x 57
Prop 65	Cancer and Reproductive Harm
Range of Cross Feeds (IPR)	.010 - .0404
Range of Inch Threads (TPI)	2-30
Range of Longitudinal Feeds (IPR)	.0023 - .0937
Range of Metric Threads	1 - 14
Range of Spindle Speeds (RPM)	36 - 1,600
Size	26 x 80
Spindle Bore (In.)	4-1/8
Spindle Mount	D1-8
Spindle Taper with Sleeve	MT-5
Steady Rest Capacity (In.)	Small 25/32 - 4-29/32, Large 3-15/16 - 9-7/16

Style (Type)	Engine - Large Spindle Bore
Swing Over Bed (In.)	26
Swing Over Cross Slide (In.)	16-1/2
Swing Through Gap (In.)	34
Tailstock Spindle Travel (In.)	6
Taper in Tailstock Spindle	MT-5
Warranty	2 Year
Weight (Lbs.)	8514
Width of Bed (In.)	16
Gross Weight	9251.0

