



JTM-1254VS with Acu-Rite 303 3X (K) DRO, X, Y & Z Powerfeeds

Product Images



Additional Information

Stock Number	JT9-698156
Column Width (In.)	14-1/4
Distance Spindle to Column (Max.) (In.)	27-3/4
Max Distance Spindle to Table (In.)	23
Model Number	JTM-1254VS
Motor (HP)	5HP, 230/460V, 3Ph
Number of Axis	3 (Knee)
Overall Dimensions (L x W x H) (In.)	92-1/8 x 79-7/8 x 104-1/4
Prop 65	Cancer and Reproductive Harm
Quill Diameter (In.)	4-1/8
Quill Down Feed Rates (IPR)	.0015-.003-.008
Range of Spindle Speeds (RPM)	80 - 3,800
Saddle Width (In.)	25-5/8
Spindle Taper (In. x TPI)	NT40
Spindle Travel (In.)	5
Style (Type)	Variable Speed NT40
T-Slot Centers (In.)	2-1/2
Table Cross Travel (In.)	15-1/3
Table Longitudinal Travel (In.)	33-7/8
Table Longitudinal Travel With Powerfeed (In.)	28-1/4
Table Size (L x W) (In.)	12 x 54
Travel of Knee (In.)	19-1/4
Travel of Ram (In.)	25
Warranty	2 Year

Work Table Weight Capacity (Lbs.)	925
Gross Weight	3696.0
Net Weight	3260.0