



JTM-1050EVS2/230 Mill With 3-Axis Acu-Rite 203 DRO (Quill) With X and Y-Axis Powerfeeds and Air Powered Draw Bar

Product Images



Short Description

JTM-1050EVS2/230 Mill With 3-Axis Acu-Rite 203 DRO (Quill) With X and Y-Axis Powerfeeds and Air Powered Draw Bar

Additional Information

Stock Number	JT9-690632
Collet Capacity	1/8 - 7/8
Column Width (In.)	20
Distance Spindle to Column (Max.) (In.)	26-3/4
Inverter Type	Delta, B
Max Distance Spindle to Table (In.)	20-3/4
Model Number	JTM-1050EVS2/230
Motor (HP)	3 HP, 230V, 3Ph
Number of Axis	3 (Quill)
Overall Dimensions (L x W x H) (In.)	66 x 63 x 87
Power Draw Bar	Pneumatic
Powerfeed	X and Y-Axis
Prop 65	Cancer and Reproductive Harm
Quill Diameter (In.)	3-3/8
Quill Down Feed Rates (IPR)	.0015 - .003 - .006
Range of Spindle Speeds (RPM)	60 - 4,500
Saddle Width (In.)	11-1/2
Spindle Taper (In. x TPI)	R-8
Spindle Travel (In.)	5
Style (Type)	EVS
T-Slot Centers (In.)	2-1/2
Table Cross Travel (In.)	14-3/4
Table Longitudinal Travel (In.)	35-1/3
Table Longitudinal Travel With Powerfeed (In.)	29-7/8

Table Size (L x W) (In.)	10 x 50
Travel of Knee (In.)	16-1/8
Travel of Ram (In.)	15-7/8
Warranty	2 Year
Work Table Weight Capacity (Lbs.)	840
Gross Weight	2580.0
Net weight	2580.0