



JTM-1 Mill With 3-Axis Newall DP700 DRO (Quill) With X and Y-Axis Powerfeeds

Product Images



Short Description

JTM-1 Mill With 3-Axis Newall DP700 DRO (Quill) With X and Y-Axis Powerfeeds

Additional Information

Stock Number	JT9-691192
Collet Capacity	1/8 - 7/8
Distance Spindle to Column (Max.) (In.)	19
Max Distance Spindle to Table (In.)	17-1/2
Model Number	JTM-1
Motor (HP)	2 HP, 230V, 3Ph
Number of Axis	3 (Quill)
Number of Spindle Speeds	16
Overall Dimensions (L x W x H) (In.)	57 x 64 x 82
Powerfeed	X and Y-Axis
Prop 65	Cancer and Reproductive Harm
Quill Diameter (In.)	3-3/8
Quill Down Feed Rates (IPR)	.0015 - .003 - .006
Range of Spindle Speeds (RPM)	80 - 5,440
Spindle Taper (In. x TPI)	R-8
Spindle Travel (In.)	5
Style (Type)	Step Pulley R8
T-Slot Centers (In.)	2-1/2
Table Cross Travel (In.)	12-1/2
Table Longitudinal Travel (In.)	23-7/8
Table Longitudinal Travel With Powerfeed (In.)	20-2/7
Table Size (L x W) (In.)	9 x 42
Travel of Knee (In.)	14-1/2
Travel of Ram (In.)	13-3/8

Warranty	2 Year
Weight (Lbs.)	2200
Work Table Weight Capacity (Lbs.)	550
Gross Weight	2200.0

