




# ETM-949, Elite 9x49 Variable Speed Mill

## Product Images

---



## Short Description

---

ETM-949, Elite 9x49 Variable Speed Mill

## Additional Information

---

Stock Number	JT9-894010
Amperage Draw @ 230V 3Ph	18
Collet Capacity	1/8 - 7/8
Distance Spindle to Column (Max.) (In.)	21-2/5
Distance Spindle to Column (Min.) (In.)	6
Gross Weight (Lbs)	2200
Head Movement (Deg.)	90°R & L 45° F & B
Max Distance Spindle to Table (In.)	18-3/4
Model Number	ETM-949
Motor (HP)	3 HP, 230V, 3 Ph
Number of Spindle Speeds	Variable
Overall Dimensions (L x W x H) (In.)	68 x 63 x 84
Overall Height (In.)	84
Prewired Voltage (V.)	230
Prop 65	Cancer
Quill Diameter (In.)	3-3/8
Quill Down Feed Rates (IPR)	0.0015 - 0.003 - 0.006
Range of Spindle Speeds (RPM)	60 – 4,500
Spindle Taper	R8
Spindle Taper (In. x TPI)	R-8
Spindle Travel (In.)	5
Style (Type)	Variable Speed
T-Slot Centers (In.)	2-1/2
T-Slots Number and Size (In.)	3 - 5/8
Table Cross Travel (In.)	12

Table Longitudinal Travel (In.)	35
Table Size (L x W) (In.)	9 x 49
Travel of Knee (In.)	16
Travel of Ram (In.)	14
Warranty	3 Year Elite
Weight (Lbs.)	2200
Work Table Weight Capacity (Lbs.)	550
Gross Weight	2450.0

